

Now you are ready to undertake **CLIPSO fitting projects**.

- when opening your shipment – CLIPSO logo in front of you – some important points:
- manipulate the fabric with **clean gloves** and wear clean worksuit
- The fabrics should not rub on the floor or any dusty object (furniture, worksuit...). Beware of it when placing the fabric.

**Tip: use the plastic cover of the fabric to protect the fabric when manipulating it.**

- Important: think **to take the sticker stapled on the fabric**, it indicates the batch number and allow us the product tracking if requested in our quality approach. If a customer service occurs, **this sticker is the only element that will help us identifying your product and intervening**

**Tip: to avoid losing this reference, staple it on the ceiling (before the fitting and at best at the entrance door level, 1st left corner)**

- You are now on the way to fit the fabric in the profiles. You will find the practical details on the attached technical sheets.

Some reminders:

- Use **the proper tools**: spatulas, cutting knife with new blades
  - Do not hesitate to add extra fabric in the profile groove
  - Always finish you work at the corners
- 
- Trim the edges with a 0,5 cm margin using a knife with new blade.
  - After verifying the tension of the ceiling, push the margins with the spatula to reinforce the tension and give a perfect finition
  - Proceed to installation of devices: spotlights, ventilation (cutting the fabric, AC). Always use low tension spotlights and hermetic bulbs.